

Witness Trees	Inches in Diameter	Bearings	Distances in Links	Witness Trees	Inches in Diameter	Bearings	Distances in Links
Hycamore	8	S 72½° W	47½				
Elm.	48	S 60° E	16½				
Wateroak	3	S 7½° E	40				
"	4	S 2½° W	46½				
Nichory	6	N 50° E	4				
Ash	3	S 2° W	24½				

Mose S Ryans et. al.

Apr. 13th 1915

By agreement I met Mose S Ryans, Frank Rogers, Cornelius Lenty, George J Lenty and H F Simmons and made the following survey on above date in section 36 T 10 R 1 W. as per plat and notes we had for assistants Cornelius Lenty Haskel Turner chairman, Narden Pauley flagman.

We then proceeded to make the following survey established the ^{east} $\frac{1}{2}$ m.p. witnessed by:

1 { 6 yeamore 8" S $72\frac{1}{2}^{\circ}$ W $47\frac{1}{2}$ lks.
elm 48" S 60° E $16\frac{1}{2}$ "

This stone is 25 lks N of the proper place to get it out of the branch

perpetuated the N.E. corner by marking

2 { water oak 3" S $7\frac{1}{2}^{\circ}$ E 40 lks
water oak 4" S $2\frac{1}{2}^{\circ}$ W 46 "

established a stone at the $\frac{1}{2}$ distance between the N.E. corner and E $\frac{1}{2}$ m.p. witnessed by

3 { Hickory 6" N 50° E 4 lks
Ash 3" S 2° W $24\frac{1}{2}$ "

L. M. Bowers